





550W STAINLESS STEEL SUBMERSIBLE DIRTY WATER PUMP VIBAS550

The 550W Submersible Pump for Dirty Water is the robust and efficient solution for drainage needs in dirty water or debris-filled environments. With a powerful 550W motor, this pump offers an impressive flow rate of up to 10,500 liters per hour, ensuring rapid drainage and runoff. Its 7m manometric height allows it to pump water from locations with a slope, and its maximum immersion depth of 7m makes it ideal for wells, cesspits, and other contaminated water removal applications. The durable stainless steel design ensures greater longevity and resilience in harsh environments, while the IPX8 system provides protection against water ingress, making it ideal for continuous submersion. The pump handles particles up to 35mm, making it easy to pass solids and maintain a steady flow. The 10-meter electrical cable offers flexibility in various installation setups, and the 35°C maximum fluid temperature expands its range of use.

Key features

- > Flow rate of up to 10,500 L/h for fast drainage.
- > Allows particles up to 35mm to pass through.
- > Up to 7m of depth.
- > Stainless steel structure with IPX8 protection.
- > Connection options of 1", G1", and 36mm.
- > 10m electrical cable for greater mobility.

Specifications

| Dimensions | 155 x 160 x 325 mm | |
|-------------------------|--------------------|--|
| Max. liquid temperature | 35º C | |
| Max. manometric height | 7 m | |
| Max. particle size | 35 mm | |
| Maximum flow rate | 10500 L/h | |
| Maximum immersion depth | 7 m | |
| Outlet - hose | 25 32 mm | |
| Outlet - threaded | 1" 1/2" | |
| Packaging dimensions | 220 x 160 x 370 mm | |
| Power cord | 10 m | |
| Product weight | 4,2 Kg | |
| Rated power | 550 W | |
| Supply voltage | 230 V 50 Hz | |
| Watertightness | IPX8 | |
| Weight with packaging | 4,6 Kg | |

Page 1 of 1 December 08, 2025, 03:18h vito-tools.com