



## LARGE FILTER 2L

### VIFAPG

This 2L water filter, with 1" (25.4mm) inlet/outlet, is ideal for protecting pumps and hydraulic systems against dirt and harmful particles. With a maximum pressure of 6 bar and a flow rate of 30 L/min, it is perfect for water supply systems in individual homes and for use as a pre-filter in pool purifiers. It is also efficient in filtering rainwater, ensuring the system operates efficiently. With support for temperatures up to 40°C, the filter is easy to remove and clean, maintaining system efficiency and extending its lifespan.

### Key features

- > **Effective protection for pumps and hydraulic systems:** This 2L water filter protects your equipment from dirt and harmful particles, ensuring efficient operation.
- > **1" (25.4mm) Inlet/Outlet:** Compatible with various water supply systems, offering versatility in installation.
- > **Maximum pressure of 6 bar and flow rate of 30 L/min:** Ideal for use in individual homes and as a pre-filter in pool purification systems.
- > **Rainwater filtration:** Maintains water quality and ensures the system's optimal performance.
- > **Supports temperatures up to 40°C:** Resistant to different conditions, maintaining effectiveness in a variety of applications.
- > **Easy to remove and clean:** The filter can be easily removed and cleaned, prolonging the system's lifespan and maintaining operational efficiency.

### Specifications

Capacity	2L
Diameter	1" (25,4 mm)
Maximum flow rate	30 L/min.
Maximum pressure	6 bar
Maximum temperature	40°C