



SINGLE-PHASE GENERATOR 2.8KVA VIG28

Due to the machine's efficiency in supplying electricity, this model is ideal for both domestic and small professional environments, guaranteeing power in the event of a power cut or failure. This manual start generator is equipped with two 16A Schuko sockets (2x 230V), making it compatible with a wide range of appliances. In addition, this small model includes wheels and a handle, which enhances its portability and increases user comfort. The single-phase generator is certified according to the Euro 5 standard and CE certification, guaranteeing that it complies with the strictest emission control and safety standards.

Key features

- > Manual start-up;
- > Circuit breaker to protect against overloads and short circuits;
- > Thermal protection for DC terminals;
- > Automatic Voltage Regulator (AVR) protecting connected equipment against electrical fluctuations;
- > Reduction of the risk of electric shock, ensured by the earth terminal;
- > Equipped with wheels and a handle for mobility and transport of the machine;
- > Two built-in 16A Schuko sockets (2x 230V).

Specifications

Automatic voltage regulator AVR	Yes
DC terminals thermal protection	Yes
Earth terminal	Yes
Engine	4-stroke combustion
Engine displacement	196 cc
Engine oil	15W-40
Fuel	Petrol
Generator	Single-phase
Manual engine start	Yes
Maximum power - AC sockets	2,8 kW
Maximum temperature	40 °C
Maximum working height	1000 m
No-load Speed	3000 rpm
Oil crankcase capacity	0,6 L
On/off switch	Yes
Protective circuit breaker	Yes
Rated current - AC sockets	230V AC 50Hz
Rated current - DC terminals	8,3 A
Rated power - AC sockets	2,5 kW
Rated voltage - DC terminals	12 V
Sound power level (LWA)	96 dB(A)
Tank capacity	15 L

Autonomy	7,5 h
Max. Power	2,8 kVA
Power factor (cos Ø)	1
Rated power	6,5 cv / 4,8 kW

Variants**Reference**

VIG28

VIG28