



THREE-PHASE GENERATOR DUAL POWER 6.5KVA VIG65TDP

Due to the machine's efficiency in supplying electricity to both single-phase and three-phase equipment, this model is ideal for small residential and business environments, guaranteeing power in the event of a fault or power cut. This generator, which can be started electrically or manually, is equipped with an ATS (Automatic Transfer Switch) connection, 1x single-phase 32A industrial socket (230V), 1x single-phase 16A Schuko socket (230V) and 1x three-phase 32A industrial socket (400V), making it compatible with various appliances. In addition, this small model includes wheels and a handle, which enhances its portability and increases user comfort. The three-phase generator is certified according to the Euro 5 standard and CE certification, guaranteeing that it complies with the strictest emission control and safety standards.

Key features

- > Versatility and efficiency, thanks to the Dual Power feature that allows the same power to be used in single-phase and three-phase;
- > Electric or manual start-up;
- > Circuit breaker to protect against overloads and short circuits;
- > Thermal protection for DC terminals;
- > Automatic Voltage Regulator (AVR) protecting connected equipment against electrical fluctuations;
- > Reduction of the risk of electric shock, ensured by the earth terminal;
- > ATS connection that enables automatic start-up in the event of a power failure;
- > Equipped with wheels and a handle for mobility and transport of the machine;
- > 1x single-phase 32A industrial socket (230V), 1x single-phase 16A Schuko socket (230V) and 1x three-phase 32A industrial socket (400V) incorporated.



Specifications

Automatic voltage regulator AVR	Yes
DC terminals thermal protection	Yes
Earth terminal	Yes
Engine	4-stroke combustion
Engine displacement	420 cc
Engine oil	15W-40
Fuel	Petrol
Generator	Single-phase Three-phase
Manual engine start	Yes
Maximum power - AC sockets	6,5 kW
Maximum temperature	40 °C
Maximum working height	1000 m
No-load Speed	3000 rpm
Oil crankcase capacity	1,1 L
On/off switch	Yes
Protective circuit breaker	Yes
Rated current - AC sockets	230V / 400V AC 50Hz
Rated current - DC terminals	8,3 A

Rated power - AC sockets	6,0 kW
Rated voltage - DC terminals	12 V
Sound power level (LWA)	97 dB(A)
Tank capacity	25 L
Autonomy	6,5 h
Max. Power	6,5 kVA
Power factor (cos Ø)	1
Rated power	15 hp / 11,2 kW