



TELESCOPIC DRYWALL SANDER 710W VILGE710



710W extensible drywall sander, with a no-load speed of 800-1700rpm (round backing pad), and a speed of 3000-6000rpm (triangular backing pad), round backing pad diameter of 260mm, triangular backing pad diameter of 293mm, Velcro-type sanding disc diameter of 215mm, velcro-type triangle sanding sheet diameter of 280mm, 2 position auxiliary handle, 4.5 metre long suction hose, for the most professional and high quality work.

Key features

> Suction system that keeps the space clean. - Variable speed according to user needs. - Lockable on/off switch. - Suction power control and rotation speed control to suit the needs of the task. - Velcro-type fastening , LED lights.



Specifications

Height	340 mm
Length	740 mm
Maximum handle extension	1,6 m
No-load speed - round sanding backing pad	800 - 1700 rpm
No-load speed - triangle sanding backing pad	r 3000 - 6000 rpm
On/off switch lock button	Yes
Power cord	4,2 m
Product weight	5.302 kg
Quick fitting of the velcro pads	Yes
Rated power	710 W
Round sanding backing pad	260 mm
Round Velcro backing diameter	215 mm
Sound power level (LWA)	99 dB(A), k = 3
Suction hose length	4,5 m
Suction system compatible with vacuum cleaner	Yes
Triangle backing pad size	293 mm
Variable speed	Yes
Velcro-type fastening	Yes
Weight with packaging	11.068 kg
Width	245 mm