

W/R



## HIGH-PRESSURE WASHER WR3 150 BAR

VIML150WR3

Its sturdy body gives it robustness and the induction motor (2000W) with aluminium head allows it to withstand intensive use, guaranteeing the high-pressure washer's reliability. It includes a built-in detergent tank, a hose (5m), a handle and wheels for easy moving and transporting of the machine.

### Key features

- > Aluminum body and pump head
- > 5-meter PVC hose
- > Extendable handle, automatic shutdown, and adjustable jet



### Specifications

Ajustable handle	Sim
Automatic stop and adjustable jet	Yes
Body	Aluminium
Carrying handle	Yes - Telescopic
Engine	Induction (copper)
Flow rate	6,3 L/min
Head	Aluminium
Height	810 mm
Hose	PVC (5 m)
IP code	IPX5
Length	400 mm
Max. inlet water pressure	7 bar
Maximum flow rate	7,5 L/min
Maximum pressure	150 bar
Operating pressure	115 bar
Operating temperature	5 - 50 °C
Power cord	5 metros
Product weight	18.451 kg
Rated power	2000 W
Sound power level (LWA)	85,2 dB(A), k = 3
Supply voltage	230 V AC 50 Hz
Weight with packaging	21.000 kg
Width	370 mm