



## ROTARY HAMMER 1050 W VIMP1050P



1050W rotary hammer with an impact energy of 9 J, a no-load speed of 0-480rpm, an impact frequency of 0-3750ipm. It has a SDS-Max chuck, 2 functions, to perform all your activities with quality

### Key features

> SDS-max chuck, high power and impact supported by an anti-vibration system, it guarantees excellent performance in the toughest and most demanding jobs. - Its metal body guarantees greater durability of the machine thanks to its robustness. - Chisel position adjustment, Safety clutch device.



### Specifications

Auxiliary handle vibration (ah) - chiselling	<b>13,1 m/s<sup>2</sup></b>
Auxiliary handle vibration (ah) - drilling	<b>12,7 m/s<sup>2</sup></b>
Carrying case	<b>BMC</b>
Chisel position adjustment	<b>Yes</b>
Chisel positions	-
Concrete drilling diameter	<b>22 mm</b>
Core bit maximum diameter	<b>55 mm</b>
Drill bit maximum diameter	<b>38 mm</b>
Drill chuck	<b>SDS-Max</b>
Functions	<b>3</b>
Impact energy	<b>9 J</b>
Impact frequency	<b>0 - 3780 ipm</b>
Main handle vibration (ah) - chiselling	<b>14,9 m/s<sup>2</sup></b>
Main handle vibration (ah) - drilling	<b>15,3 m/s<sup>2</sup></b>
Motor type	<b>Carbon brushes</b>
No-load Speed	<b>0 - 480 rpm</b>
Power cord	<b>2 m</b>
Safety clutch	<b>Yes</b>
Sound power level (LWA) - chiselling	<b>107 dB, K = 3</b>
Sound power level (LWA) - drilling	<b>105 dB, K = 3</b>
Sound pressure level (LpA) - chiselling	<b>96 dB, K = 3</b>

### Package Contents

Included accessories: - Point chisel 18x350 mm
- Flat chisel 18x350 mm
- Drills 16-18-20x350 mm
- Aux. Handle.

Sound pressure level (LpA) - drilling **94 dB, K = 3**

---

Body **Metal**

---

Height **370 mm**

---

Length **440 mm**

---

Product weight **6.745 kg**

---

Weight with packaging **11.404 kg**

---

Width **130 mm**

---

Insulation class **II**

---

Rated power **1050 W**

---

Supply voltage **230V AC 50Hz**

---