




COMBINED CIRCULAR SAW 1200 W - 210 MM

VISCC12210

1200W combined circular saw with a no-load speed of 4200rpm, 24-teeth blade with 2mm blade thickness and 210mm blade diameter, to help you carry out all your work safely and effectively.

Key features

> 1200 W of power, cutting angles up to 45°, ergonomic handle and blade protection system, this combined circular saw is highly robust and reliable.



Specifications

(Bevel) Max. width x cutting depth 45°/0°	110 x 33 mm
(Bevel) Max. width x cutting depth 45°/45°	80 x 33 mm
(Miter) Max. width x cutting depth 0°/0°	110 x 55 mm
(Miter) Max. width x cutting depth 0°/45°	80 x 55 mm
Adjustable rip fence	Yes
Adjustable swivel table from 45° up to + 45	Yes
Blade diameter	210 mm
Blade hole diameter	30 mm
Clamp	Yes
Cutting angle (bevel)	0° / 45°
Cutting angle (miter)	- 45° / 0° / + 45°
Disc thickness	2 mm
Lower blade guard	Yes
Maximum cutting depth	30 mm
No-load Speed	4200 rpm
Number of teeth on the blade	24
Parallel guide	Yes
Rear table support	Yes
Side support bars	Yes
Sound power level (LWA)	113 dB(A), k = 3
Height	305 mm
Length	420 mm
Product weight	8.649 kg

Weight with packaging	10.149 kg
Width	410 mm
Rated power	1200 W