



## ROTARY HAMMER 850 W VIMP850

850W rotary hammer with an impact energy of 2,75 J, a no-load speed 0-1100rpm, an impact frequency of 0-5200ipm. It has a SDS-Max/Plus chuck, 3 functions, to perform all activities with quality.

### Key features

> Featuring a SDS-plus chuck, variable speed, 3 functions and included accessories, this reliable and versatile work tool is suitable for a wide range of concrete drilling jobs. - Chisel position adjustment, speed variation, reversible direction of rotation, on/off switch lock button, safety clutch device.



### Specifications

Auxiliary handle vibration (ah) - chiselling	<b>13,1 m/s<sup>2</sup></b>
Auxiliary handle vibration (ah) - drilling	<b>14,1 m/s<sup>2</sup></b>
Carrying case	<b>BMC</b>
Chisel position adjustment	<b>Yes</b>
Chisel positions	-
Concrete drilling diameter	-
Core bit maximum diameter	-
Drill bit maximum diameter	-
Drill chuck	<b>SDS-Plus</b>
Functions	<b>3</b>
Impact energy	<b>2,75 J</b>
Impact frequency	<b>0 - 5200 ipm</b>
Main handle vibration (ah) - chiselling	<b>15,7 m/s<sup>2</sup></b>
Main handle vibration (ah) - drilling	<b>15,8 m/s<sup>2</sup></b>
Motor type	<b>Carbon brushes</b>
No-load Speed	<b>0 - 1100 rpm</b>
On/off switch lock button	<b>Yes</b>
Power cord	<b>2 m</b>
Reverse rotation	<b>Yes</b>
Safety clutch	<b>Yes</b>
Sound power level (LWA) - chiselling	<b>103 dB, K = 3</b>

### Package Contents

Included accessories: - Point chisel 14x250 mm
- Flat chisel 14x250 mm
- Drills 8-10-12x320 mm
- 1 Rule   Aux. handle..

Sound power level (LWA) - drilling	-
Sound pressure level (LpA) - chiselling	<b>92 dB, K = 3</b>
Sound pressure level (LpA) - drilling	-
Variable speed	<b>Yes</b>
Dimension	<b>365 x 85 x 220 mm</b>
Product weight	<b>3,11 Kg</b>
Weight with packaging	<b>5,48 Kg</b>
Insulation class	<b>II</b>
Rated power	<b>850 W</b>
Supply voltage	<b>230V AC 50Hz</b>
Packaging dimensions	<b>385 x 115 x 315 mm</b>